

## GAS UNIT

### Be protected in minutes

FireAvert is plug-n-play ready. Simply plug into the back of the stove, connect the gas valve, and sync it to the closest smoke alarm. FireAvert is activated by the smoke alarm, turning off the gas to the stove and oven when the smoke alarm is sounding.

FireAvert helps mitigate your risk of having a kitchen fire. See video below. [See video below.](#)



### Features

- No batteries and maintenance free.
- No professional install needed.
- Fits in the void space behind most gas stoves.
- Reusable with a 25 year expected life.
- Resets at the electrical panel.
- Light indicates number of times activated.
- Sound detection of smoke alarm from up to 60 feet away.



Gas Stove | A-G04-5-15



[See How Easy It Is To Install](#)

## Installation Process

FireAvert is plug-n-play ready. Simply plug it into the back of the stove. FireAvert is activated by the smoke alarm, cutting power to the stove and oven when the smoke alarm is sounding. To reset the stove after it cuts off power simply flip the stove breaker off and then back on again, and press the button on the FireAvert red box. This will enable your stove to begin working again.

# GAS UNIT

## Electrical Specifications

Operating Voltage	120v
Amperage	12.5 amps 60Hz
Plug Configuration	NEMA 5-15 R/P
Pole	2
Wire	3 wire grounding
Fire Rating	Housing ABS fire retardant - UL94(5Va,V-0,V-1,V-2,HB)

## Physical Specifications

Dimensions	3 ¾ inches (9.52 cm) x 2 inches (5.08 cm) x 3 ¾ inches (9.52 cm) – (LxWxH)
Weight	.9 LB (0.408 Kg)
Metal Valve Weight	.9 LB (0.408 Kg)
Color	Black
Operating Temperature Range	32°F to 90°F (0°C to 33°C)
Operating Humidity Range	0 to 80% RH non-compensating
Mounting	None required. Plugs directly into NEMA 5-15R outlet for electrical
Environmental	RY PB Free

## LED Modes

LED Mode	White LED	Green LED	Red LED	Blue LED
Gas Safety Mode	Off	Off	Off	On
Power Up	Flash	Off	Flash (Cut Count)	
Standby	Off	Solid	Off	
Protection Mode	Off	Off	Solid	

## Solenoid Specifications

Dimensions	Inlet Sizes ½ inch NPT outlet Sizes - 15/16 inch UNF Inlet Sizes ½ inch NPT outlet Sizes - 3/4inch UNF
Max Inlet Pressure	½ psi (14" W.C.)
Ambient Temperature	Maximum 175°F Minimum 0°F
Electrical Rating	6VDC/Max Amp : 600mA
Model	GM919 - Natural Gas Only - 100,000 BTU/Hr Rates are for 1,000 BTU/Hr, 0.64 Sp. Gr. gas for natural gas and 2,500 BTU/Hr
Certification	ANSI Z21.21-2015•CSA 6.5-2015 Automatic Valves for Gas Appliances

## Certifications

UL 498A Certification | CSA 22.2 Certification | FCC Certification



## Warranty

[Click Here](#) to download the FireAvert Warranty